

# HANSA T15

PRECISION EQUIPMENT



## SPECIFICATIONS



**CAPACITY**  
14000L/14m<sup>3</sup>



**MAX SPREAD WIDTH**  
36m Urea / 58m SSP



**MAX WEIGHT**  
20000kg





## STANDARD FEATURES AND OPTIONS

<b>Tyres</b>	- 650/65-30.5 flotation tyre *others available upon request	●
<b>Tarp</b>	900 grade rollover with flipover centre pole	○
<b>Load Cells</b>	When selected with ISOBUS rate controller auto rate calibration is enabled.	○
<b>Brakes</b>	Hydraulic Air	○ ○
<b>Rate controller</b>	ISOBUS (auto rate cal when selected w/ scales option) HANSA 7" screen (rate and spinner control) TOPCON TRIMBLE *others available upon request	○ ○ ○ ○
<b>Section control</b>	Twin conveyor for headland and section control (Available with most rate controllers)	□
<b>Suspended drawbar</b>	Rubber absorption pads	● -
<b>Hydraulic jack</b>		●
<b>Mudguards</b>	Plastic molded	○
<b>Axle</b>	Single 2400mm track BPW 10/335 Single 3000mm track BPW 10/335 Tandem 2400mm track hydraulic susp. Tandem 3000mm track hydraulic susp. *others available upon request	● ○ ○ ○
● <b>STANDARD</b>	- <b>NOT APPLICABLE</b>	
○ <b>OPTION</b>	□ <b>OPTION (factory fitted)</b>	

## TECHNICAL DATA

<b>Capacity (L/m<sup>3</sup>)</b>	14000/14
<b>Tare Weight</b>	6200kg
<b>Max Payload (Kg)</b>	20000
<b>Loading Height (A)</b>	2900mm
<b>Bin Length (B)</b>	4500mm
<b>Overall Length (C)</b>	7600mm
<b>Overall Height (D)</b>	3050mm
<b>Hitch Height (E)</b>	500mm
<b>Bin Width (F)</b>	2300mm
<b>Overall Width (G)</b>	2950mm
<b>Standard Wheel track</b>	2400mm
<b>Bin construction (material)</b>	Stainless steel
<b>Conveyor width</b>	750mm wide
<b>Spinner configuration</b>	Twin hydraulic driven
<b>Spinner drive</b>	48cc Permco Gear motors W/Series/Parralel block.
<b>Conveyor drive</b>	60mm driveshaft, hydraulic drive, 20:1 reduction box
<b>Filtering</b>	High pressure filtering on spinner and conveyor circuit
<b>Warranty</b>	12 months (1 year)
<b>Control</b>	PWM Full Hydraulic
<b>Hydraulic Configuration</b>	Switchable – closed centre load sensing to open centre fixed

